

LOCK SWITCH



HRL LOCK SWITCH

ELECTRICAL & MECHANICAL SPECIFICATION

Switch Rating: 1A @24V ac/dc Life: >10,000 Cycles

Proof Voltage: 750 Vac (Initial) Lock Type: 5 Disc

Insulation Resistance: >999M Ω @ 500Vdc (Initial) Operating Temperature: -20°C to +65°C

 Contact Resistance:
 <20mΩ (Initial)</td>

 Lock Housing:
 Zinc Alloy Bright Cr Plated

Contact Material: Brass CZ108, Ag Plated **Moulding Material**: Polyamide 6.6 G.F. VO Rated

Moulding Colour: Single pole – Grey, Double pole - Green

Reinforced module to lock connection for higher vibration or weight applications

FEATURES

Front assembly 2 keys per switch
Up to 200 differ key
Single or Double pole combinations available

Rear panel depth - <30mm

Keys are double entry (can be inserted into lock either way up)


Max panel thickness 4.5mm

Moulded bezel available for parallel lock headed version (SRL02101 see below)

Made In UK




SINGLE POLE LOCK SWITCH



PARALLEL LOCK HEAD 90° INDEXING

BASIC PART No.	TOTAL MOVEMENT	INDEXING	KEY WITHDRAWAL POSITIONS	SWITCH CONFIGURATION
HRL-5-A	90°	90°	1,4	2
HRL-5-B	90°	90°	1 ONLY	3
HRL-5-C HRL-5-R HRL-5-S	180° 180° 180°	90° 90° 90°	1,4,7 1,4 1 ONLY	1 OFF 2 3
HRL-5-N	180°	90°	1,4,7	1

SINGLE POLE LOCK SWITCH



Key Withdrawal

For centre off, link pins 1 & 3, Types T and Q only




TAPERED LOCK HEAD 90° INDEXING

BASIC PART No.	TOTAL MOVEMENT	INDEXING	KEY WITHDRAWAL POSITIONS	SWITCH CONFIGURATION
HRL-5-D	90°	90°	1,4	2
HRL-5-E	90°	90°	1 ONLY	13
HRL-5-F HRL-5-V HRL-5-W	180° 180° 180°	90° 90° 90°	1,4,7 1,4 1 ONLY	1 OFF 2 3
HRL-5-P	180°	90°	1,4,7	1
HRL-5-T	180°	90°	1,4,7	12
HRL-5-Q	180°	90°	4 ONLY	3 — OFF

DOUBLE POLE LOCK SWITCH

Parallel lock head 60° indexing




PARALLEL LOCK HEAD 60° INDEXING

BASIC PART No.	TOTAL MOVEMENT	INDEXING	KEY WITHDRAWAL POSITIONS	SWITCH CONFIGURATION
HRL-5-J	60°	60°	1,3	
HRL-5-K	60°	60°	1 ONLY	

DOUBLE POLE LOCK SWITCH

Tapered lock head 60° indexing




TAPERED LOCK HEAD 60° INDEXING

BASIC PART No.	TOTAL MOVEMENT	INDEXING	KEY WITHDRAWAL POSITIONS	SWITCH CONFIGURATION
HRL-5-L	60°	60°	1,3	
HRL-5-M	60°	60°	1 ONLY	=:

OPTIONAL MOULDED BEZEL

FOR PARALLEL LOCK HEADED VERSIONS _

PART NUMBER SRL02101



HRL ORDERING CODE

